

TREMstop CIPP Tub Box

A pass through cast in place device with an adapter for tub drains

Product Description

TREMstop CIPP Tub Box is both a concrete sleeve and a firestop. The base or foot consists of a plastic housing, intumescent material and a neoprene gasket. Extending up from the base is a plastic adapter that creates a rectangular blockout in the concrete. Foam blocks are placed in the adapter and set the height of the unit.

TREMstop CIPP TubBox is attached to the deck before the concrete pour. When the pipe is ready to be installed, the foam is removed and the pipe is passed through the unit.

Basic Uses

TREMstop CIPP Tub Box is used for metal and plastic pipe penetrations through concrete and fluted deck floors.

Features and Benefit

TREMstop CIPP Tub Box has a tough plastic housing that will stand up to the rigors of a concrete pour, but will not rust once installed. The rectangular blockout leaves room in the concrete slab to easily install the tub drain.

The use of foam to extend the height allows for easy accommodation of varying and uncommon slab thicknesses.

Applicable Standards

UL 1479 (ASTM E-814), UL 263 (ASTM E-119), CAN4-S115M, CAN/ULC-S101M

Packaging

TREMstop CIPP Tub Box is available at standard preset heights of 8" and 9". All other preset heights are made to order. Specify height when placing order.

TREMstop CIPP Tub Box 1.5" – 2" 5/case

Color

White Adapter, green base

Availability

TREMstop CIPP Tub Box is immediately available from your local Tremco representative or distributor throughout the United States and Canada.

Application/Installation

TREMstop CIPP Tub Box is for use in firestop systems. Attach TREMstop CIPP Tub Box to plywood or metal deck using smooth bore nails. Ensure foam is attached to the top of the unit. After the concrete is set, remove the foam and pass pipe through the TREMstop CIPP Tub Box.

See installation guide included in case or firestop system for further detail.

Limitations

Not recommended for use with passive fire containment systems not listed or approved by Tremco.

Warranty

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

TYPICAL PHYSICAL PROPERTIES

Property

Tub Box Blockout Dimensions	12.25" x 9.25" (311 mm x 235 mm)
Minimum Slab Thickness	5" (127 mm)



Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357