

## TREMstop CIPC Water Closet

**A coupling style cast in place device with an adapter to fit a water closet**

### Product Description

TREMstop CIPC Water Closet is both a concrete sleeve and a firestop. It consists of a translucent foot that fits inside the bottom of the unit and is removed with the formwork, two standard couplings and a PVC riser pipe to adjust the height. A cap is placed on the top of the unit to prevent the concrete from pouring in.

TREMstop CIPC Water Closet is attached to the deck before the concrete pour. The translucent foot is removed with the formwork. When the pipe is ready to be installed, remove the cap and glue the pipe into the bottom and the water closet flange into the top.

### Basic Uses

TREMstop CIPC Water Closet is used for PVC pipe penetrations in conjunction with water closet installations through concrete and fluted deck floors.

### Features and Benefits

TREMstop CIPC Water Closet has a tough plastic housing that will stand up to the rigors of a concrete pour, but will not rust once installed. The top coupling fits a standard water closet flange.

The use of riser pipe to extend the height allows for easy accommodation of varying and uncommon slab thicknesses. Custom units can be ordered to a preset height to accommodate the specific needs of the project.

### Packaging

TREMstop CIPC Water Closet is available at standard preset heights of 8" and 9". All other preset heights are made to order. Specify height when placing order.

TREMstop CIPC Water Closet 3"	8/case
TREMstop CIPC Water Closet 3" w/Flange	8/case
TREMstop CIPC Water Closet 4"	6/case
TREMstop CIPC Water Closet 4" w/Flange	6/case

### Applicable Standards

UL 1479 (ASTM E-814), UL 263 (ASTM E-119), CAN4-S115M, CAN/ULC-S101M

### Color

White

### Availability

TREMstop CIPC Water Closet is immediately available from your local Tremco representative or distributor throughout the United States and Canada.

### Application/Installation

TREMstop CIPC Water Closet is for use in firestop systems. Attach TREMstop CIPC Water Closet to plywood or metal deck using screws. Ensure cap is attached to the top of the unit. After the concrete is set, remove the translucent foot with the form and solvent weld pipe into bottom of TREMstop CIPC Water Closet. Solvent weld water closet flange into top of TREMstop CIPC Water Closet.

See installation guide included in case or firestop system for further detail.

### Limitations

Not recommended for use with passive fire containment systems not listed or approved by Tremco.

### Warranty

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

## TYPICAL PHYSICAL PROPERTIES

### Property

Minimum Slab Thickness

### Results

6" (152 mm)



FIRESTOP DEVICE FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS  
SEE UL FIRE RESISTANCE DIRECTORY  
Control No. 59S2

### Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906  
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213  
1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357