

TREMstop D

A pre-fabricated firestopping collar

Product Description

TREMstop D is a firestopping collar comprised of intumescent material and a metal restricting collar. The intumescent expands during a fire to fill the void left as combustible penetrations burn away and the metal restricting collar directs the intumescent action inward. A variety of sizes are available and fit industry standard pipe sizes.

Basic Uses

TREMstop D is used with plastic pipe in concrete assemblies, wood floor/ceiling assemblies and gypsum walls. It can also be used with fluted metal decks.

Features and Benefits

TREMstop D is easy to install and easy to inspect. The distinctive green color clearly identifies it as a part of a firestop system. The variety of sizes makes firestopping larger diameter pipes easy.

Applicable Standards

UL 1479 (ASTM E-814), UL 263 (ASTM E-119), UL 723 (ASTM E-84), CAN4-S115M, CAN/ULC-S101M

Packaging

TREMstop D 1.5 (3.8 cm)	12/case
TREMstop D2 (5.1 cm)	10/case
TREMstop D3 (7.6 cm)	10/case
TREMstop D4 (10.2 cm)	6/case
TREMstop D6 (15.2 cm)	2/case
TREMstop D8 (20.3 cm)	2/case
TREMstop D10 (30.5 cm)	1/case

Sizes greater than 10 in. available upon request.

Color

Green

Availability

TREMstop D is immediately available from your local Tremco representative or distributor throughout the United States and Canada.

Application/Installation

TREMstop D is for use in firestop systems. Wrap the device around the penetrating item, insert the tab into the slot and bend back. Slide the device flush with the wall or floor. Mechanically fasten TREMstop D using the amount of fasteners detailed in the firestop system. Fasteners should be located symmetrically around the device. See firestop system for further detail.

Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

Warranty

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.



FIRESTOP DEVICE FOR USE IN
THROUGH-PENETRATION FIRESTOP SYSTEMS
SEE UL FIRE RESISTANCE DIRECTORY
59S2

Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357