

## TREMstop MP

### A firestopping putty pad

#### Product Description

TREMstop MP is a moldable putty preshaped into three pad sizes to fit different electrical boxes. Release liners are on both sides of the pad and one must be removed for installation.

#### Basic Uses

TREMstop MP is for use with metal and plastic electrical outlet boxes in gypsum wall assemblies.

#### Features and Benefits

TREMstop MP is pliable and has excellent adhesive strength making installation by hand fast and easy. One side of the release liner can be left in place keeping hands clean during installation. The thickness of the pad prevents tearing on the corners of metal outlet boxes.

#### Applicable Standards

UL 263

#### Packaging

6" x 7" x .2" (152 mm x 178 mm x 51 mm)

12 pads/case

7.25" x 7.25" x .2" (184 mm x 184 mm x 51 mm)

12 pads/case

9.25" x 9.25" x .2" (235 mm x 235 mm x 51 mm)

12 pads/case

#### Color

Rust Red

#### Availability

TREMstop MP is immediately available from your local Tremco representative or distributor throughout the United States and Canada.

#### Application/Installation

TREMstop MP is for use in firestop systems. Remove the release liner from one side of the pad. Align the pad to the side of the box, overlapping the stud. Cut slits in the pad to fit around conduit or cables. Adhere TREMstop MP to the back of the electrical outlet box. Reshape the pad to fit around the box. Trim excess corners and mold to the inside of the conduit fittings connected to the box. Remove the exposed release liner, if desired.

#### Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

#### Warranty

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

### TYPICAL PHYSICAL PROPERTIES

Property	Test Method	Results
STC Information	ASTM E-90	Restored to 61 in a U411 wall



WALL OPENING PROTECTIVE MATERIAL  
FIRE RESISTANCE CLASSIFICATION  
SEE UL FIRE RESISTANCE DIRECTORY  
59S2