

TREMstop WS

A graphite-based intumescent wrap strip

Product Description

TREMstop WS is made of a flexible graphite-based intumescent compound. It is designed to expand when exposed to a fire to fill any voids left as the combustible materials burn away.

Basic Uses

TREMstop WS is used with plastic pipe in concrete assemblies, wood floor/ceiling assemblies and gypsum walls. It can also be used with fluted metal decks.

Features and Benefits

TREMstop WS is flexible enough to easily wrap around the pipe. It can be used in conjunction with TREMstop MCR to field-fabricate a firestop collar for applications with odd angles or annular spaces. TREMstop WS is packaged in rolls rather than precut strips to reduce waste and accommodate a variety of pipe diameters with one product.

Applicable Standards

UL 1479 (ASTM E-814), UL 263 (ASTM E-119), UL 723 (ASTM E-84), CAN4-S115M, CAN/ULC-S101M

Packaging

TREMstop WS 1.4 1.4" x 41' Rolls 5 rolls/case
TREMstop WS 2.4 2.4" x 41' Rolls 3 rolls/case

Color

Dark Gray

Availability

TREMstop WS is immediately available from your local Tremco representative or distributor throughout the United States and Canada.

Application/Installation

TREMstop WS is for use in firestop systems. Wrap TREMstop WS around the penetration, secure and slide into the annular space. See firestop system for further detail including the number of wraps, method of securing and annular space.

Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

Warranty

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.



FILL, VOID OR CABITY MATERIAL FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS
SEE UL FIRE RESISTANCE DIRECTORY 59S2

Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357